

### T-646 APPLICATION SYSTEMS

#### Consistent tape placement at reduced cycle times

T-646 Application Systems semi-automatically apply strips and/or spots of many adhesive transfer and double-coated tapes to flat surfaces. Features of both application systems include the following:

- Product conveying speed up to 150 ft/min.
- Accommodates product up to 1 ¼" thick
- Accommodates ½" to 1" wide tape – 2" optional.
- Two applicators standard – will accommodate up to four applicators
- Individual tape programming
- Touch screen operator interface.
- Displays characters in English, French or Spanish
- Displays numbers in inches or millimeters
- Product batch count
- Optional catch tray for taped product
- 115v/230v, 50/60Hz power input capability
- CE approved
- Also available in 43" and 55" widths



T-646I Application System  
Product Up To 18" wide  
Shipping weight 275 lbs.



T-646WI Application System  
Product Up To 30" Wide  
Shipping weight 300 lbs.



#### SF-20 Feeder & AS-20 Alignment Section

- Accommodates product widths up 18"
- Provides continuous top load of product
- Accommodates flexible product up to 1/8" thick
- Helps increase productivity
- Shipping weight 165 lbs.
- Available for 30" wide product

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.