

**NEW****MODEL SF-60/SD-60 AUTOMATIC TAPING SYSTEM (500 FPM)**

The SF-60/SD-60 Automatic Taping System automatically feeds and applies transfer tape with liner in place and tear strip tape to a corrugated or paperboard blank.

**METHOD OF OPERATION**

Using this machine the operator manually loads the product in a hopper and starts the machine. The automatic feeder feeds the blanks to a conveyor where one or more tapes are applied automatically at speeds up to 500 feet per minute (152.4 MPM), depending on the tape

and the product. The product is then conveyed out of the machine for additional processing. Top loading of feeder permits loading while machine is operating.

**OPTIONAL FEATURES**

- Multiple tape applicators to apply several lanes of tape in one pass
- Dual taping heads with an automatic switching system for the transfer tape for continuous operation when one roll runs low
- Downstream processing equipment including stackers and shingling conveyors
- Variety of tape applicators including tear tape, adhesive transfer tape, magnetic and foams

**PRODUCT SPECIFICATIONS**

Product Size: 12" (305mm) to 60" (1,524mm) wide; 12" (305mm) to 78" (1981mm) long

Product Thickness: 15 point (0.4mm minimum paperboard)

Tape Roll Sizes: Tear Strip Tape-15" (381mm) OD x 7" (178mm) high, 6" (152mm) ID Core  
Transfer Tape-18" (457.2mm) OD, 3" (76.2mm) ID Core

**MACHINE SPECIFICATIONS**

Electrical: 240 VAC, 3PH, 60 Hz.

Size: 16' (4.88m) long x 5' (1.52m) wide x 5.5' (1.68m) high

Speed: Up to 500 (152.4 m) per minute

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.