

MODEL M-635 ASSEMBLY AID DISPENSER

The M-635 Assembly Aid Dispenser is designed for use with Assembly Aid Positioning Adhesive to provide a convenient roll-up liner system. A turn of the handle and additional break-away adhesive is exposed to permit instant adhesive coating of parts. The use of this system enables accurate positioning and holding of parts and components.

OPERATING INSTRUCTIONS

1. Press the part onto the Assembly Aid web located over the dispenser rubber pad.
2. Pull the part away from the Assembly Aid web.
3. Turn the crank to wind up the used liner web and advance new Assembly Aid adhesive forward into position over the rubber pad ready for use.
4. To remove the spent liner, loosen the thumb screw and remove the rewind assembly with the spent liner from the unit. Remove the liner from the rewind drum. Replace the rewind assembly and tighten the thumb screw.



PRODUCT SPECIFICATIONS

- Tape: Assembly Aid Positioning Adhesive
- Tape Width: 6" (144 mm)
- Tape Roll Size: 6" (150 mm) max. on a 3" diameter core
- Size: 10½" long x 8¾" high x 11" wide
- Weight: 7 lbs. (Unpackaged)

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.