

MODEL PTA/T-627-2 PROTECTIVE TAPE APPLICATOR

The Model PTA/T-627-2 Protective Tape Applicator is designed to apply a protective pressure sensitive tape to flat products up to 2" wide. Using this machine an operator manually feeds the product into variable speed nip rollers.

The PTA/T-627-2 applies up to a 2" wide pressure sensitive tape to the top surface of the product cutting and holding the tape for the next application.

To be mounted on a bench or table

OPTIONS

- Grooved drive rollers for special contoured products.
- Tape low or tape fail sensors.
- AB PLC controls.
- Wider tape application – up to 7½".
- Variety of tapes for other purposes can be used.

PRODUCT SPECIFICATIONS

- Tape Width: ¼" – 2"
- Tape Roll Size: 18" (457mm) OD – 3" (115mm) ID Core
- Tape Accuracy: $\pm 1/8$ "
- Tape Lengths: 1" – 99" or longer on special applications



MACHINE SPECIFICATIONS

- Electrical: 115V, 1Ph, 60Hz, 30A
- Air: 80 PSI (550 kPa)
- Size: 12" deep x 36" wide x 36" high
- Speed: Up to 100' per minute
- Weight: 150 lbs. approximately

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.