

### MODEL WL-50 LINER PULL TAB APPLICATOR

The model WL-50 Liner Pull Tab Applicator dispenses, cuts and seals 3M #5400 or Y4230 heat bond tabbing film ½" to 1 ¾" wide to the release liner on 3M acrylic foam tape. The tabs are typically applied to the ends of the tape or the joints between tapes for ease in removal of liners exposing the high strength adhesive.

#### FEATURES


- Designed to heat seal one or more tabs to the tape liners.
- Fixturing provides accurate location of the product and actuation of the machine.
- Accurate temperature, time and pressure controls provides consistent heat sealing of the tabs to the liner.

#### OPTIONS

- Soft touch
- Floor frame
- Full guarding

#### PRODUCT SPECIFICATIONS

Film:	3M #5400 or Y4230 heat bond tabbing film
Film Width:	½" (12.7mm) minimum 1 ¾" (44.4mm) maximum
Film Roll Diameter:	10" roll on a 3" core
Film Lengths Dispensed:	1 ¾" ± 1/16" (44.4mm)
Tab Extension From End of Tape:	1 ¾" (31.8mm) maximum
Film Placement Tolerance:	± 1/16" (1.5mm)



#### MACHINE & POWER SPECIFICATION

Electrical:	120V, 1Ph, 50/60 Hz, 10A
Optional:	220V, 1Ph, 50/60 Hz, 5A
Air:	80 psi (550 kPa) 4.5 SCFM
Size:	29" long x 16" wide x 30" high
Weight:	52 lbs (23.6kg)
Cycle time:	2 seconds per cycle, plus load/unload time

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.